

UL Product iQ®



JDYX7.E197390 - Fuses, Supplemental Certified for Canada

Fuses, Supplemental Certified for Canada

OPTIFUSE

E197390

Suite C

1675 Pioneer Way

El Cajon, CA 92020 United States

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
Supplemental fuses: cartridge enclosed				
TCE	4.6 x 14.2 (0.18 x 0.56)	0.1-8	125Vac	10000
		0.1-8	250Vac	200
		0.1-8	350Vac	100
Supplemental fuses: filled-tube				
FPK	10.3 x 38 (0.41 x 1.50)	0.1- 0.375	600Vac	100000
		0.4-2	600Vac	100000
		2.5-5	600Vac	100000
		6-12	600Vac	100000
		15-30	600Vac	100000
		0.1- 0.375	600Vdc	10000
		0.4-2	600Vdc	10000
		2.5-5	600Vdc	10000
		6-12	600Vdc	10000
		15-30	600Vdc	10000
Supplemental fuses: pigtail leads, cartridge enclosed				
TCE-P	4.6 x 14.2	0.1-8	125Vac	10000

	(0.18 x 0.56)			
		0.1-8	250Vac	200
		0.1-8	350Vac	100
Supplemental fuses: time delay, filled-tube				
TPK Time delay. Otherwise non-time delay.	10.3 x 38 (0.41 x 1.50)	3.15-8	500Vac	10000
		9-12	500Vac	10000
		15-30	500Vac	10000
		0.3-3	500Vac	10000

Last Updated on 2021-07-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."